



THE CONTRACTORS BOOKLET

...making life simple!

Scolmore[®]
GROUP

www.scolmore.com

IP65 Inceptor®
Nano⁵ Fixed

IP54 Inceptor®
Nano⁵ Adjustable



Poised and Ready

TAKE THE STING OUT OF LENGTHY INSTALLATIONS, WITH THE PRE-WIRED FLOW™ CONNECTOR

The Inceptor® Nano⁵ range comprises two compact, fire-rated, dimmable downlights, which pack an array of features into their shallow profile. The Nano⁵ consumes less power and produces a comparable light output while reducing the size and cost.

With a highly competitive price point for the features and benefits offered, the new high-performance, 4.8W LED lighting products are designed to have mass market appeal and are suitable for a variety of uses in domestic applications.

Fire rating 30, 60 and 90 minute. Acoustic: OdB (zero impact on sound insulation)
Airflow: BS 5250: 2002 compliant.

IP65
FIXED

60MM
CUT OUT

IP54
ADJUSTABLE

75MM
CUT OUT



Pre-wired Flow™ connector

Flow™ is Click® Scolmore's pre-wired connection system designed to speed up installation and allows even faster removal for testing and replacement of components.



Shallow recess depth with a powerful SMD light source, paired with a 40° multi-faceted, halogen-effect lens for exceptional light quality.

Newly designed, dependable and independently verified fire-rated structures, combined with trademark intumescent band ensures maximum safety in the event of a fire.

There is the choice of 3 different finishes; chrome, satin chrome and white, as well as fixed and adjustable options.

LED

2
YEAR
WARRANTY

2700K
WARM WHITE

4000K
COOL WHITE

Insulation support bracket

Compatible with Inceptor® Nano[®] downlights

ISC1020 sold separately





IP65 Inceptor®
Omni Fixed

IP54 Inceptor®
Omni Adjustable

Omni Tricolour

3 SWITCHABLE COLOURS ALL IN ONE FITTING; WARM WHITE, COOL WHITE AND DAYLIGHT

Existing technology found in the current Inceptor® products and innovative new features have been combined within one fitting, providing cutting-edge features at a competitive price. Key features include an adjustable colour temperature switch, allowing the selection of colour temperatures to suit the installation. Flexibility and ease of installation are the key factors in the design of this product. The fitting also has the option to change bezels from a fixed version to adjustable option if required.



Interchangeable fixed & adjustable bezels

Adjustable bezel sold separately



Switchable colour temperature

The Omni features a built-in three position switch which grants the ability to change the colour temperature instantly.

The Inceptor® Omni combines cutting-edge chip-on-board LED technology and a custom built multi-faceted lens to deliver a quality of light comparable to traditional light sources such as halogen lamps.

Insulation support bracket

The removable insulation support clip fixes directly onto the Omni. This means insulation is lifted away from the unit, maintaining a minimum air space and helping any generated heat to dissipate. Lowering the temperature around the fitting can extend the life of the unit.

5 YEAR WARRANTY

Only valid once registered online at www.scolmore.com

Features:

- Flow™ connector for quick, easy connection
- Compact size, fits into a 65mm+ void depth
- Intumescent collar offers a 30, 60 and 90 minute fire-rating
- Fire, air-flow and acoustic rated
- Double insulation so no earthing is required
- Available in 3 finishes; chrome, satin chrome and white



Small Fitting, Big Features

IT'S GOT A LOT TO SMILE ABOUT

The Inceptor® Pico offers a cost effective LED solution whilst producing an excellent light output for the power utilised. The fitting combines a number of key features which sets it apart from competitor products. The Inceptor® Pico is ideal for installations where the void depth is limited, and is an ideal solution for non fire-rated applications.

As well as being suitable for variable ceiling board thickness whether plasterboard or wooden panelling, the Pico has an adaptable cut-out and will fit apertures of 65mm to 75mm diameter.

Available in
our 3 most popular
finishes...

chrome, satin chrome and white



SMD LED technology

Surface mounted LED have high reliability performance and utilise very little power, resulting in low energy consumption which offers a cost saving solution against that of traditional lamps.

Energy efficient

The Inceptor[®] Pico has an energy saving rating of A⁺ and an L70 LED lifetime of 20,000 hours resulting in zero maintenance and low energy consumption for the lifetime of the product.

Screw down cable-grip

A terminal cover with built-in cable-grip both saves time and ensures that no strain is placed on the terminal connections.



Loop in and out terminals

Loop in and out terminals allow easier connection of multiple fittings (daisy-chain). The fitting is double insulated so no earth is required.



2700K
WARM WHITE

4000K
COOL WHITE

Epic Output Tiny Fitting

FIRE RATED, FIXED INTEGRATED LED DOWNLIGHT

Following on from the success of the original Inceptor® Pico we heard your requests for a fire rated version and so the Pico FG was born.

Ideal for installations where the void depth is limited and fire rating is required. Pico FG has an adaptable cut-out to fit apertures of 70mm to 75mm diameter, and is suitable for install into ceiling thicknesses of up to 36mm due to its heightened spring brackets.

Pico FG utilises a lens constructed from high quality polycarbonate. The frosted front provides improved beam angle resulting in smoother light distribution. Once installed, ingress protection is applied making the Pico dust tight and offers protection against low pressure water jets, an ideal solution for kitchens, bathrooms and wet rooms.

Available in 3 finishes...

chrome, satin chrome and white



Compatible with Click[®] Smart

Dimmable as standard Pico FG can be easily switched or dimmed utilising a variety of methods.

Energy efficient

The new Pico FG has an energy saving rating of A+ and an L70 LED lifetime of 20,000 hours resulting in zero maintenance, low energy consumption for the lifetime of the product.

30cm Fly Lead

The pre attached fly lead provides easier installation for contractors.

Insulation Support Clip

The Insulation Support Clip has been developed to allow installers to lay thermal insulation directly over the top of the Inceptor[®] Pico FG. It creates a 20mm air-space above the driver which allows air to circulate and cool. This allows the driver to dissipate heat more effectively and in-turn allows the luminaire to run cooler.



ISC1020



Evolution of Lighting

REVOLUTIONARY DESIGN MAKING FOR EASIER INSTALLATION

The Inceptor® Evo was born with the contractor in mind, installation of the bulkhead is made faster with the addition of the Flow™ connector. Simple removal of the surface mount adaptor ring allows the product to be semi-recess mounted with ease.

Available in two designs; circular and eyelid. Both utilise opal optical-grade polycarbonate diffusers and a reinforced, impact-resistant polycarbonate body. The product is double insulated and an earth-loop terminal is provided for convenience.

flow™

Fast-fit integrated Flow™ connector

Saves time during install



As well as providing 2 styles of fascias, the Evo is also available with 4 distinct modes of operation:

- 3 hour emergency and microwave sensor
- 3 hour emergency
- Microwave sensor
- Standard driver

LED

IP65

4200K
COOL WHITE

3
YEAR
WARRANTY

Metal enclosure fittings

The robust polycarbonate construction (IK08) can be enhanced further by encasing the body in an additional metal enclosure, providing excellent vandal resistant protection (IK10).

The Inceptor® Evo can be used in a wide range of places and environments. The choice of three different metal fascias grants the opportunity to create a perfect look.

Circular

A Circular fascia allows light to be distributed at an optimum beam angle of 120°.



Eyelid

The Eyelid fascia reduces upward glare, providing greater direction and emphasis of illumination.



Grille

For architectural and design settings the Grille is a perfect fascia which also reduces glare.



Die-cast aluminium body

A die-cast aluminium body ensures a high grade surface finish.

Four side entry points

The metal enclosures offer the same cable entry locations as the Evo's polycarbonate main body; with the four side entries sealed with removable inserts.



OA411AG
OA401AG



OA412AG
OA402AG

Whatever the Weather

IP66 WEATHERPROOF SOCKETS AND SWITCHES

The IP66 rated weatherproof socket and switch enclosures offer users a single fix installation - with the whole of the back box fixing to the wall to accommodate the socket or modules. Multiple knock-outs on each side (20mm) allow for entry from all angles, and more...

| Product code | Description | |
|--------------|---|--|
| OA411AG | 1 Gang 2-way weatherproof switch | Fitted with a 2-way MiniGrid® module |
| OA412AG | 2 Gang 2-way weatherproof switch | Fitted with 2 x 2-way MiniGrid® modules |
| OA035AG | 1 Gang weatherproof socket | Fitted with a 1 Gang Mode® switched socket |
| OA036AG | 2 Gang weatherproof socket | Fitted with a 2 Gang Mode® switched socket |
| OA401AG | 1 Gang weatherproof switch enclosure | Modules supplied separately |
| OA402AG | 2 Gang weatherproof switch enclosure | Modules supplied separately |
| OA501AG | 1 Gang weatherproof unfurnished enclosure | |
| OA502AG | 2 Gang weatherproof unfurnished enclosure | |

New and improved design...

the lid is now designed to stay open to aid installation.



OA035AG
OA501AG

OA036AG
OA502AG

Robust construction

- Polycarbonate construction
- Flexible rubber base allows for mounting on most types of uneven surfaces
- UV protected against fading
- Smooth operation of switches
- Neutral modern design suitable for most locations
- High impact resistance
- Ergonomic design

Multiple gland entry position

- Multiple knockouts (20mm) for entry from all angles

Weatherproof - IP66

- Offers high level of protection against ingress of water jets and dust

Multiple switch configurations

- Designed to fit any MiniGrid[®] modules (13A max)



MINIGRID[®]

The Aequip66[®] range uses the MiniGrid[®] system's interchangeable switch modules (13A max), allowing multiple switch configurations.



GridPro[®] puts you in Pole Position

A VERSATILE RANGE OF 20A GRID PRODUCTS

A comprehensive range of finishes and modules available to offer ultimate flexibility. As well as a wide range of modules to choose from all of our switch modules are 20A rated so they are ideal for both domestic and commercial applications.

The GridPro[®] range will complement your existing Click[®] installation, as the range was specifically designed to seamlessly match our existing ranges of Click[®] wiring accessories.

One module fits all

... via a clipping feature and screw attachment on each module




Ergonomic modules

GridPro[®] features design elements that enable quicker and easier installation whilst maintaining all the key features and stylish design of the existing range of Click[®] wiring accessories.

All modules come with backed off captivated terminal screws for ease of assembly.

A screwdriver guide ensures the screwdriver easily locates with terminal screw head to clamp the cable in position. The terminal screw apertures are designed to help guide the tool.





Horizontal fixing screws

GridPro® frontplates have horizontal mounted screws to give a uniform, aesthetic look throughout the range.




Standard BS4662 back boxes

A unique feature of 1 - 4 Gang GridPro® frontplates is that any British Standard BS4662 flush mounted back boxes can be used. This is because our 1 - 4 Gang GridPro® frontplates do not require a yoke!*

*excluding the screwless Definity™ GridPro® frontplates, which have their own dedicated inserts.

No Yoke!

... for 1 - 4 Gang GridPro[®] frontplates




No Yoke!

The GridPro[®] modules are secured to the back of the 1 - 4 Gang GridPro[®] frontplates via the screw feature on the modules*. The benefit of not using a yoke is that it allows the installer to use standard back boxes!

*excluding the screwless Definity[™] GridPro[®] frontplates, which have their own dedicated inserts.

Screw directly on to the back of 1-4 Gang GridPro[®] frontplates!





Universal yokes

The GridPro® modules are secured to the back of the 1 - 4 Gang GridPro® frontplates via the screw feature on the modules*. The benefit of not using a yoke is that it allows the installer to use standard back boxes!

*excluding the screwless Definity™ GridPro® frontplates, which have their own dedicated inserts.



Clip-on modules

When a yoke is required on the multi-tier GridPro® frontplates the module can be assembled using the clip attachment, which secures them to the metal yokes.

For use with 6 - 24 Gang GridPro® frontplates*

*excluding the screwless Definity™ GridPro® frontplates, which have their own dedicated inserts.



Now offering in house laser etching on our GridPro[®] modules!



Laser etching

Let us save you time and money and do the module etching for you! Completely customisable modules, offering you and your customers a wider variety of options.

Contact us for more information.



All GridPro[®] modules are available in eleven distinctive, quality finishes, with black or white inserts, excluding antique brass and black nickel finishes, which are available with black inserts only.

Module finishes available: Antique Brass (AB), Black Nickel (BN), Pearl Nickel (PN), Polished Brass (BR), Polished Chrome (CH), Satin Brass (SB), Satin Chrome (SC), Brushed Stainless (BS), Stainless Steel (SS), Black (BK) and Polar™ White (PW).



Keeping **US** Boosted

1 AND 2 GANG SWITCHED SOCKETS WITH USB

Eliminate the need for bulky chargers and free up your plug sockets with 1 and 2 Gang switched socket with integrated USB! The convenient USB port is centrally located to avoid cable interference from anything that may be plugged into the sockets. Our 1 and 2 Gang switched sockets with single USB outlet are available in 98 plate designs and finishes within the Click[®] brands. This provides flexibility for use in various locations i.e. lounges, kitchens, bedrooms and offices.

Our retrofit sockets have a depth of just 20mm and can be comfortably mounted into a 25mm back box. 1 Gang version requires 35mm with 47mm in Define[®] and Definity[™].



Available
in 98 plate
designs...

with black or
white inserts.



USB output 5 volt 2 amps

Suitable for most tablets, smart phones, cameras and other USB devices, all of which can still be used whilst charging! Our single USB output guarantees optimum charge rate regardless of the device charging.

Safety

Tested and complies with UK safety and EMC requirements and is in-line with EU legislation. The USB socket ranges also benefit from short circuit protection, so should there be a short on the output the power supply will shut down and reset after the short circuit has been removed.

Twin earth terminals


For a simple connection of the earth conductor.



MODE[®]



CMA812



CMA735

Mode[®] Made Easy

A STYLISH, CONTEMPORARY AND FLEXIBLE RANGE OF SMOOTH PROFILE WIRING ACCESSORIES

The smooth, modern lines of the Mode[®] accessory plate will fit easily into traditional and contemporary designs alike. Mode[®] accessories provide flexibility with a comprehensive selection of products ranging from a standard light switch and socket outlet through to more specialised products dealing with the very latest developments in entertainment media interfaces.

We've shown just a sample of the Mode[®] range. To see the full range or for more details, log onto www.scolmore.com and register for your free wiring accessories catalogue, or download the Mode[®] section.

Easy installation...

with earth terminals at the top of the product.



Click[®] Mode accessories have been designed with the electrician in mind, by designing our products with earth terminals at the top of the product for easy installation.

Mode[®] accessories have been conceived and developed as a high quality, flexible and modern solution to virtually any domestic wiring requirement.

Interchangeable modules

Simple, single screw fixing of modules offers the simplest possible means of installing and replacing modules.

The modular design of Mode[®] allows designers and installers unprecedented flexibility in creating dedicated wiring solutions to deal specifically with actual wiring needs.



Antimicrobial certified products

All white moulded and Mode[®] Part M wiring accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.99% kill off rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella and Klebsiella Pneumoniae.



Switching to us is Key

HOTEL KEY CARD SWITCHES

Our key card switch acts as the main electrical switch for the room and is operated by the guests', reducing the amount of time the lights (and/or appliances) are left on. All lighting and heating facilities only become operational once a corresponding card is inserted into the key card switch, so no needless heating, cooling or lighting of an unoccupied space takes place. When the key card is removed the controlled circuits remain under power for a further 10 seconds to 5 minutes, which can be adjusted by the hidden potentiometer under the cover plate. This helps ensure a safe exit from the room before the power is turned off.

Compatible with hotels' entry system cards. Suitable for standard cards and credit cards 85.60mm x 53.98mm.



The hotel key card switch comprises of 3 separate products. Providing versatility to compliment any decor or existing Click® wiring installations, with interchangeable mounting and cover plates.



LED indicator

Locate the key card switch in the dark via the power LED indicator, so no additional lighting is required to turn the key card switch on.

Suitable for controlling lighting circuits

Suitable for switching inductive loads of 6AX and resistive loads of 10A. Larger loads such as sockets and air conditioning can be connected via contactors. Connection terminals suitable for 2 x 1.5mm² cable.

1. Mounting plate
2. Key card timer switch module
3. Finishes to complement all Click® decorative and white moulded ranges...





Overload Protection for Ventilation Equipment

It has been noted that some manufacturers of ventilation equipment (fans) are not installing internal fuses to protect the equipment. Instead the manufacturers are stating within their installation literature the fan requires overload protection via a 1, 3 or 5 amp fuse.

Regulation 134.1.1 of BS7671:2008 incorporating amendment No 1:2011 does require electrical equipment to be installed in accordance with the instructions provided by the manufacturers of the equipment.

Simple
 single screw
 installation...
 of the modules



CMA020PW

CMA047PW

CMA403

As standard across our moulded and decorative ranges we offer a 10A 3 pole fan isolation switch and a fused connection unit module all in one switch plate. Saving you valuable time and money!

Simple, single screw installation of the modules on the plate allows contractors to devise and install customised switching solutions on site.



Module finishes available:

Antique Brass (AB), Black Nickel (BN), Pearl Nickel (PN), Polished Brass (BR), Polished Chrome (CH), Satin Brass (SB), Satin Chrome (SC), Brushed Stainless (BS), Stainless Steel (SS), Black (BK), Polar™ White (PW) and Click® White (WH).

Select your
 plate and
 modules...
 then assemble



Plate finishes available:

Antique Brass (AB)
 Black Nickel (BN)
 Brass (BR)
 Chrome (CH)
 Pearl Nickel (PN)

Satin Brass (SB)
 Satin Chrome (SC)
 Stainless Steel (SS)
 Brushed Stainless (BS)

Also available:

Black (BK)
 Polar™ White (PW)
 Click® White (WH)

Interchangeable dimmer switch modules:

MD9010 1-10V analogue dimmer module
 (25 x 62 x 22mm)

MD9001 6A 2 way push on/off (non-
 dimmable) module (25 x 62 x 22mm)

MD9022 250W/Va 2 way resistive/ inductive
 dimmer module (25 x 62 x 22mm)

MD9042 400W/Va 2 way resistive/ inductive
 dimmer module (25 x 62 x 22mm)



MD150CH

Module mounting kit in polished
 chrome finish
 Dimmer module not supplied.

We've shown just a sample of the MiniGrid® range. To see the full range or for more details, log onto www.scolmore.com and register for your free wiring accessories catalogue, or download the MiniGrid® section.



Eliminate Flickering
Trim the brightness easily
with DIP switch.



Never Resets
Easy to program
and never loses your
installation settings.



Two Dimmers In One
Simply change between
leading and trailing edge
with DIP switch.

The only Dimmer you'll ever need

Suitable for dimming on a conventional 2 way circuit our new 100W dual mode dimmer with trim function is much easier to program than regular dimmers because of the two small switches on the back of the module. This allows the dimmer to be programmed without removing from the plate.


Small Module Size

Fits into Minigrid[®] and GridPro[®] mounting kits.

- Can be placed above/below each other on multi-tier plates.
- Will fit into 25mm back box when used on raised plates.
- Will fit into 35mm back box when used on flat plates.
- Interchangeable with the MD9022 and MD9042 in our dimmer plates.



CODE: MD9014



1 **Switch 1** allows the minimum brightness to be adjusted

2 **Switch 2** allows the dimming mode to be adjusted

Thermal Overload Protection

If the module gets too hot it will cut out without damaging the internal electronics, allowing the module to cool down. This will not reset installation settings.



MD023

MD004

MD029

Module finishes available: Antique Brass (AB), Black Nickel (BN), Pearl Nickel (PN), Polished Brass (BR), Polished Chrome (CH), Satin Brass (SB), Satin Chrome (SC), Brushed Stainless (BS), Stainless Steel (SS), Black (BK), Polar™ White (PW) and Click® White (WH).

Interchangeable modules:

| | |
|-------|---|
| MD023 | 20A double pole (twin width) switch modules |
| MD009 | 10AX 2 way 'paddle' switch module (triple width) |
| MD004 | 2 way 'ingot' switch modules |
| MD047 | 13A fused connection modules |
| MD029 | 13A resistive 10AX inductive double pole and key switch modules |

We've shown just a sample of the MiniGrid® range. To see the full range or for more details, log onto www.scolmore.com and register for your free wiring accessories catalogue, or download the MiniGrid® section.

Antimicrobial
certified
products...

perfect for
commercial
applications



PRW618

CMA612

Mode's Extended Family

Latest additions to the comprehensive Mode® range of accessories are the 12 and 18 Gang plates. Utilising the plates and the MiniGrid® modules allows contractors to devise and install customised switching solutions on-site.



Antimicrobial certified products

All white moulded and Mode® Part M wiring accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.99% kill off rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella and Klebsiella Pneumoniae.



CL512

CL518

MiniGrid[®] just got Tougher

The new 12 and 18 Gang Metal Clad switch plates offer versatility and strengthen the comprehensive selection of Metal Clad products that are already available. Electrophoretically coated plates and back boxes provide a durable and long lasting heavy duty finish to this attractive range of products.

All switch products are of modular construction allowing the installer total freedom in designing customised switching solutions according to on-site needs.

Also available:

1 and 2 Gang 13A DP Metal Clad switched socket with outboard neon rockers. Unfurnished plates and mounting boxes are available for use in conjunction with our extensive range of MiniGrid[®] and New Media[™] modules...



CL835



CL840

StudBox®



SB1G

SB2G

How StudBox® works




StudBox® 1 is 450mm long so no need to measure height from the floor on stud work.



Plasterer puts board in correct position then bangs in area of StudBox®.



Set StudBox® at marked height and insert first screw. Set level using spirit level then insert second screw.



Points on the face of the box mark exact position to cut out. No measuring required.



Push out tabs and insert cables into required box / boxes. Use snips to remove plaster board marking points off the boxes not used.



StudBox® fits tight to the back of board reducing noise and fire passage significantly. Working depth of 48mm.

No need to use your noggin!

Saves on time
and cost.



SB6IN1

OPTION 1



OPTION 2



OPTION 3



OPTION 4



OPTION 5



OPTION 6



Dimensions

SB6IN1 380mm - 450mm centres

SB1G 120mm - 600mm centres

SB2G 130mm - 600mm centres

**ONE BOX, SIX
OPTIONS AVAILABLE
WITH SB6IN1**



CLICKsmart




Control at your Fingertips

WIRING ACCESSORIES FOR A SMARTER HOME

Scolmore's range of Click® Smart intelligent wiring accessories aims to strip home automation right back to basics, offering a smart solution that has at its core, accessibility and simplicity for the end user.

The Click® Smart system makes it easy to adapt and upgrade your home to provide extra security, energy saving, comfort and control.

Complement your existing Click[®] wiring installation



Smart switches are compatible with Click[®] Smart and can be utilised with its switching and dimming receivers.

Smart switches consist of a retractive switch module and a switch cover plate, they are available in 5 switch types and multiple finishes and styles from our Click[®] wiring accessory ranges...

We have now put these components together as a simple smart code for your convenience.



RFDEL-71B

Dimming receiver



RFSAI-61B

Switching receiver



Plate Style

Product Finish

Insert Colour


Product Number

For more information visit www.scolmore.com and download the full range of Click[®] Smart switches and receivers.



CLICKsmart

Everything you need in one box - two smart solutions to make your home smarter



Solution one - Fix flickering rotary dimmers by using a retractive switch instead of a rotary dimmer (wired).

Code: CMA-SDIM1

What's in the box

- 1 x Dimming module
- 1 x Face plate
- 1 x Retractive switch module



When you switch on one of your lights with a rotary dimmer do you experience continuous flickering?



Even when the lights on, the flickering has continued.



Dealing with constant flickering can be very frustrating for you.




Make your home smarter with the RFDEL-71B and a retractive switch.



Replace the wired rotary dimmer with the retractive switch and add the RFDEL-71B to the light fitting.



This will now stop any flickering that may have occurred.



Solution two - Add a wireless switch with an outdoor socket for multiple applications.

Code: OA1636AG

What's in the box

- 1 x Aquip66[®] 2 Gang switched socket outlet
- 1 x RFSAI-61B receiver
- 1 x RFWB-20/G smart switch




There's always something to do around the house, no matter what time it is.



It's sometimes difficult to see in the dark and you never know what you are walking into.



Make your home smarter with the Click[®] Smart RFWB-20/G and RFSAI-61B.



Simply add the RFSAI-61B to the socket you wish to control.



And then add the RFWB-20/G switch to the convenient place.



By adding a smart switch you can now control anything plugged into the socket.



CLICKsmart

Create schedules
for timed automatic
control...



CSB040



RFDEL-71B



RFSAI-61B

Smart Box

WIRELESS CONTROL VIA YOUR SMART PHONE OR TABLET

We have designed a bespoke Click® Smart app which puts the functionality of your home in the palm of your hand.

Designed with simplicity in mind the smart box can be utilised within new and existing Click® Smart installations, all that's required is a broadband connection. Simply plug the smart box into one of the ethernet ports, located usually on the back of your broadband router, download the app and away you go!

We've shown just a sample of the Click® Smart range. To see the full range or for more details, log onto www.clicksmart.com or subscribe to our Youtube page to watch the videos!

Three products are all you need.

The Smart box, RF receivers and a smart phone or tablet

Smart box

The smart box itself, connected to the wireless router and a power socket outlet.

Receivers

Receivers are available in three categories - switching receivers, dimming receivers and shutter receivers.

Smart device

You can either use your mobile device or tablet to control Click[®] Smart around the house.



Download the app from the **Apple App Store** or **Google Play**



1 Smart box

All information is stored on the smart box.



40 Receivers

Each smart box can enable up to 40 receivers.



8 Devices

Up to 8 smart phones or tablets can control each receiver.



0 Controllers

No need to buy multiple controllers.



MP606CHWH

A single media plate offers one convenient point...

to combine power and media together.



MM002BK



MM002WH

The Power of Media

NEW MEDIA™ PLATES AND MODULES

The modern home is now more than a mere home. It doubles up occasionally as a cinema, concert hall, meeting venue and computer room etc. and Click® New Media wiring accessories are perfect.

10AX/13A rocker switch modules

| | |
|----------------|----------------------------------|
| MM002BK | 10AX 2 way switch - black |
| MM002WH | 10AX 2 way switch - white |
| MM025BK | 10AX intermediate switch - black |
| MM025WH | 10AX intermediate switch - white |

20A double pole rocker switch modules

| | |
|----------------|---------------------------------|
| MM022BK | 20A DP switch - black |
| MM022WH | 20A DP switch - white |
| MM023BK | 20A DP switch with neon - black |
| MM023WH | 20A DP switch with neon - white |

The MP606 is perfect for your satellite installation

Required modules:

- MM406WH Double satellite - white
- MM501WH HDMI outlet with flexible connection (80mm long) - white
- MM415WH Single male IEC (FM) - white
- MM410WH Single female IEC (TV) - white
- MM460WH Telephone master - white



New Media™ modules:

MM305WH VGA module with fly-lead - white

MM300WH USB throughput with fly-lead - white

MM496WH 3.5mm audio jack module with fly-lead - white

MM491WH Triple RCA module with screw terminals - white

MM550WH Brush module

MM515 2A USB charging outlet

MM501WH HDMI outlet with flexible connection (80mm long)




Ease of Installation is Hard-Wired into our Thinking

Connecting up a 45A cable isn't easy so Scolmore® have come up with a solution – one wire per terminal. It'll save your fingertips – and save you time.

Can be utilised with
 a 25mm deep back
 box if required

UK Design Registration No. 3015175



45A Max. dual connection plate and pattress box

Product references:
 PRW217 and PRW218

- Each incoming and outgoing cable wired independently, making installation easier
- Accepts up to 3 x 16mm² twin and earth with 45A maximum loading
- Dedicated 35mm deep pattress box



PRW218
 Pattress box
 for PRW217

PRW217
 45A Max. dual
 connection plate

Antimicrobial certified products

All white moulded and
 Polar™ wiring accessories
 are manufactured using
 Urea Formaldehyde.






Connectors, Hubs & Management Boxes

The lighting management system is a new range of additional products to the existing Flow™ range and has been designed specifically to help contractors create more complex lighting installations quickly, easily and safely. It features a number of new products that allow the quick connection, configuration and re-configuration of circuits, primarily intended for lighting.

Key features of the lighting management boxes:



- Suitable for loads up to 20A which means it can be used for more than just lighting
- Management boxes can be controlled or dimmed using suitable PIR sensors or mains dimmers
- Can incorporate wireless switching and dimming scenarios using Click® Smart products
- Durable heavy duty finish to withstand all installation requirements
- Ample fixing points to suit any method of installation



CT1016

Use the CT1016 to take control of up to 16 lights (24 using the CT350), with three different switching configurations. Easily add a switched live into a Click® Flow circuit.

- 16 way configurable box
- 1 x 16 way (1 way switching)
- 1 x 16 way (2 way switching)
- 2 x 8 way (1 way switching)
- Additional 8 ways available using CT350 splitter
- Additional way allows interlinking



CT1008

With the CT1008 you can connect up to 8 lights (16 using the CT350), or you can connect another CT1008 to the output at the end.


- 8 way box
- Connect up to 8 lights (16 using the CT350)
- Additional output allows interlinking or provides additional way



CT1300

Plug-in switch adapter easily adds a switched live into a Click® Flow circuit.

- Pre-wired with earth and neutral links
- 250V–20A plug-in connector
- Large terminals with easy access
- Terminal screws supplied raised
- Easy lock and release mechanism
- Versatile, easy-connection system



SP1016

Mounting bracket for cable suspension tray suitable for both CT1016 and CT1008 lighting management boxes.



CT300

4 pin (1 in, 3 out) Flow™ hub junction box. The hub can also be connected directly to another hub.



CT350


This splitter has been specifically designed to be slimline so that it can be used with the CT1016 and CT1008.

- Allows up to double the amount of ways
- Easy lock and release mechanism
- Versatile, easy-connection system



CT300

250V 20A 4 pin (1 in 3 out)
Flow™ hub junction box



Hubs can be linked together in a chain

The Hub

Designed to take the 3 pin or 4 pin plug-in connector versions, giving contractors the flexibility to arrange circuits easily and quickly.

- One hub can be connected directly to another or via the Flow™ link cables
- A quick and easy solution when adding lighting or appliances to an existing Flow™ circuit (can be linked up to 20A)



CT203C

- Quick release lockable covers
- 4 pin plug-in connector with auxiliary terminals
- Fast-fit cable clamps
- Auxiliary provides the opportunity for a second switched live or permanent feed for use typically with emergency lighting applications


CT103C

- Fast-fit cable clamps
- Quick release lockable covers
- 3 pin plug-in connector with loop terminal
- Cable grips for where the installation limits the fixing of the connector



CT103M


- Fast-fit cable clamps
- Quick release lockable covers
- Single male connector



CT203M


- Quick release lockable covers
- Fast-fit cable clamps
- Single male connector

We've shown just a sample of the Flow™ option. To see the full range or for more details, log onto www.scolmore.com to download our Flow™ catalogue and to view the complete range of wiring accessories.



CT102C

- 3 pin plug-in connector with loop terminal. Cable grips for where the installation limits the fixing of the connector
- Cord restraint is fitted within the male connector




CT101C

- Increased load handling with 20A rating
- Male: Max 1.5mm² 3 core cable;
Female: Max 3 x 2.5mm² twin and earth (with additional loop terminal)
- Also available on a range of FlameGuard® downlights
- Replaces the CT100C




CT202C

- 4 pin plug-in connector with auxiliary terminals
- Auxiliary provides the opportunity for a second switched live or permanent feed for use typically with emergency lighting applications



CT1300



CT1300 is pre-wired with earth and neutral links.


Switch Adaptor

We recognise that your time is money, our plug-in switch adaptor easily adds a switched live into a Click[®] Flow circuit. With easy access large terminals and fast connection.

CT1300

- 250V~ 20A plug-in connector
- Large terminals with easy access
- Terminal screws supplied raised
- Easy lock and release mechanism
- Versatile, easy-connection system





RFDEL-71F

RFSA-61F

- Flexible wireless switching
- Multiple functions
- Control wirelessly

Smart Wiring Accessories

Upgrade your electrical installation with our new Click® Smart receivers pre-fitted with Flow™ connectors.

Switching and dimming receivers

| | |
|------------------|---|
| RFSA-61F | 16A 1 channel multifunction switching receiver pre-wired with Flow™ connector |
| RFDEL-71F | 160Va 1 channel multifunction dimming receiver pre-wired with Flow™ connector |

Smart LED dimming

Dimming and controlling dimmable 230V LED light sources can be so confusing for contractors and end users but with the RFDEL-71B this is made easy.

- Suitable for dimming a single 5W dimmable LED source
- 7 programming options
- Select between capacitive, LED, resistive and inductive loads

CT1401



CT1400

CT1401

- Click® Flow ceiling rose cover
 (Not suitable for use with CT103 / CT203)

CT1400

- 4 pin plug-in ceiling rose connector with auxiliary terminals
- Auxiliary provides the opportunity for a second switched live or permanent feed for use typically with emergency lighting applications



Low smoke zero halogen pre-wired cables

- CT732** 6A 3 pole 0.75mm² to free end 2m
- CT733** 6A 3 pole 0.75mm² to free end 3m
- CT735** 6A 3 pole 0.75mm² to free end 5m
- CT742** 6A 4 pole 0.75mm² to free end 2m
- CT743** 6A 4 pole 0.75mm² to free end 3m
- CT745** 6A 4 pole 0.75mm² to free end 5m
- CT845** 20A 4 pole 2.5mm² male to female 5m



Pre-wired cables

- CT802** 6A 4 pin Flow™ extension cable 2 metre cable
- CT803** 6A 4 pin Flow™ extension cable 3 metre cable
- CT805** 6A 4 pin Flow™ extension cable 5 metre cable



Includes
Flow™ plug-in
connector...

Easy lock and
release mechanism

FlameGuard[®] & Flow[™]

We recognise that your time is money, our plug-in connector gives you easy access with large terminals and fast connection. Designed initially for lighting circuits to enable isolation of transformers, control gear etc. whilst conducting the 1000V insulation resistance test.


The FlameGuard[®] system has already been incorporated into a selection of our ranges of low voltage and mains downlights. There is a FlameGuard[®] protected, fire and acoustic rated downlight to fit virtually every installation requirement. Other related products include optional moisture seals to prevent the ingress of moisture laden air into ceiling voids or attic spaces etc. A specially developed insulation support box which facilitates the laying of an unbroken layer of insulation material directly over any FlameGuard[®] downlight installation.

FlameGuard[®] Back Boxes

PEACE OF MIND IN THE EVENT OF FIRE


- No additional components to purchase or install
- Simple and quick to install saving time and money
- Multiple cable entry points available
- Earth terminal fitted
- Durable all steel construction

Unique spring loaded lugs



NEW and improved features*

*WA4247 and WA4147 only



Upper tabs work from 5mm to 22mm

With the upper tabs removed, the lower tabs work from 15mm to 30mm



Now with second pair of gripping arms

Maximum board thickness of 30mm

Arms are designed to easily break off with pliers



WA4247



WA4237



WA4135

FlameGuard[®] back boxes have been tested and conform to both fire and acoustic standards BS EN 1364-1: 2015, Acoustic BS EN ISO 140-3:1995. Complies with Building Regulations. Fire tested up to 90 minutes with the capability of the boxes being mounted back to back.

essentials™




deco®

Working Side by Side

The 1 + 2 dual accessory galvanised steel back boxes (WA370 and WA375) have been designed to allow all Deco® products to be fitted side by side with the supplied gaskets. This provides the neatest installation of Deco® accessories possible.

Our Deco® range is available in 9 distinctive quality finishes: antique brass, polished brass, polished chrome, satin chrome, satin brass, black nickel, pearl nickel, stainless steel and georgian style cast brass.



Click Together with the Click[®] Connector

Ezylink (GA100) dry lining wall box connector simply connects most combinations* of Click[®] dry lining boxes to provide the neatest installation of cavity boxes possible.

*Ezylink not suitable for use with WA108P





The updated site now incorporates a number of improved features that allow users to access new information directly and easily:

- Ordering 24 hours a day 7 days a week with the ability to check current stock levels as required, meaning you are not restricted to ordering during normal office hours
- Access to on-line catalogues will keep you fully updated with the complete product range and provide information on new products as and when they become available
- The order tracking service keeps you up to date with the progress of your shipment
- Managing your administration paper work is now even easier with instant access to reports and essential documents at a click of a button
- A 'quick buy tab' and the ability to store the most common orders for repeated use, adds to the versatility and flexibility of the revised system.

To register: E-mail us at sales@scolmore.com or call our Sales Office on 01827 63454

Are you a Click® stockist?

If so, you automatically have access to the Marketing Hub. Download all our latest literature, flyers to personalise and our full range of images for use on your website or artwork. Follow the links from www.scolmore.com for more information.

So, why not click and find out how we can help you?



Visit www.scolmore.com to see our new website, packed with new features and easier navigation.





Subscribe to our YouTube channel for our latest product and installation videos! Just search 'Click Scolmore'.

You can also find us on:



facebook.com/ClickScolmore



twitter.com/ClickScolmore



linkedin.com/company/scolmore-international-limited



Download the free app today from the app store by searching 'scolmore'.

The new app from Click® Scolmore allows you to use your phone to browse our complete range of products, add products to your favourites or to the quote basket. The app then allows you to email the contents of the basket back to yourself providing all the information you need to obtain any quotations.

Features include:

- Downloadable catalogues
- Quote basket
- Scolmore news
- Product videos
- Electricians tool kit
 - Zs calculator
 - Downlight no. calculator
 - Cable selection and volt drop calculator
 - Resistance calculator
 - KVA converter
 - Voltage calculator
 - Cost saving calculator
 - Current calculator
 - Power calculator



United Kingdom

Scolmore[®]
G R O U P

Scolmore Park, Landsberg,
Lichfield Road Industrial Estate,
Tamworth, Staffordshire
B79 7XB United Kingdom

T: +44 (0)1827 63454
F: +44 (0)1827 63362
E: sales@scolmore.com

www.scolmore.com

Southern Ireland

click[®] Litehouse

18 Corrig Road,
Sandyford Industrial Estate,
Dublin,
D18 WV79 Ireland

T: +353 (1) 2811 122
F: +353 (1) 2811 224
E: sales@clicklighthouse.ie

www.clicklighthouse.ie

MAR7801/6